




Brava Old World Slate



Brava Old World Slate Light Arendale



Brava Old World Slate Onyx



Brava Old World Slate Charcoal



Brava Old World Slate Atlantic

Beautifully authentic high-performance roofing.

The beautiful look of a slate roof without the maintenance.

Truly realistic

Our proprietary process creates the most authentic-looking old world slate on the market.

Superior performance

Brava is designed to withstand even the most severe weather, boasting the highest hail resistance rating in the industry.

Enhanced curb appeal

Curb appeal directly correlates with owner satisfaction and higher property value.

Maintenance free

Brava's proprietary formulation ensures extreme durability.

Color technology

Brava's proprietary multi-coloring process means you get the authentic appearance of a natural product, complete with variegated colors throughout the entire product.







Fully sustainable

Brava uses recycled material to create a roof that is fully recyclable.

Complete

Brava offers a complete line of accessory tiles.

Unparalleled Performance



Description	Weight	Dimensions
6" Field Tile	1.4 lbs.	6" x 22"
9" Field Tile	1.8 lbs.	9" x 22"
12" Field Tile	2.7 lbs.	12" x 22"
Starter	1.6 lbs.	12" x 12"
Hip & Ridge	2.0 lbs.	5 5/8" x 6" x 16"
Solid Multi-Width Accessory	4.5 lbs.	12" x 22 7/8"
Weight Per Square		311 lbs./sq.

Aesthetics	Brava Old World Slate	Natural Slate
Authentic Look	✓	✓
1" Thickness	✓	
Multi-Colored Variegated	✓	Only the most expensive
Solid Accessories for Realistic Installation	✓	✓

Performance	Brava Old World Slate	Natural Slate
Fire Retardant: Class A or Class C	✓	✓
Wind Resistance: 188+ mph*	✓	
Impact Resistance: Class 4	✓	Varies by product
Freeze/Thaw Resistant	✓	May spall in alpine regions
Maintenance Free	✓	Requires inspection and repair throughout the life cycle
Colorfast	✓	Only some varieties
Hail Warrantied	✓	

Installation	Brava Old World Slate	Natural Slate
Lightweight	✓	
Estimated Waste Factor	Low	High; slates with hairline cracks or broken during install will be discarded
Gun Nailed in Cold Weather	✓	



*Brava tiles are tested and approved to withstand wind speeds of up to 188 mph with nails and up to 211 mph with high wind / screw installation.

Tolerances +or- 1/2". All specifications subject to change without notice.

The printed colors shown may vary from actual colors. Before making a final selection, be sure to review actual material samples and roof installations. Please contact your salesperson for further assistance.

In order to achieve certain fire and wind ratings, special installation instructions may be required. Please reference Brava Roof Tile installation manuals at www.BravaRoofTile.com for more details.